

LVD 2K70 No Emergency Kit

 With Emergency Kit (Standard Temperatures)

 With Emergency Kit (Low Temperatures)

	INPUT VOLTAGE	120 - 277 Vac		
	INPUT FREQUENCY (Hz)	45 - 65		
	POWER CONSUMPTION (W)	40	45	45
	LUMINOSITY (lm)	2700		
	OPERATING TEMPERATURE	-30°C to +50°C	0°C to +50°C	-30°C to +50°C
	STORAGE TEMPERATURE	-40°C to +70°C	-30 °C to + 65°C	-30°C to +65°C
(* Recommended storage temperature +5°C to +25°C)				
	BATTERY LIFE	-	4 Years	4 Years
	EMERGENCY AUTONOMY & LUMINOSITY	-	Table 1	Table 1
	BATTERY FULL CHARGE TIME (h)	-	24	24
	WEIGHT (kg)	2,25	2,6	2,6
	DIMENSIONS (mm) [LxWxH]	321 x 160 x 102		
	IP RATING	IP 65		
	IK RATING	IK 05		
	COLOR TEMPERATURE (CCT)	Cool White: 5.000 - 7.000K		
	LED WORKING LIFE	50 000 h typical		
	CERTIFICATIONS	CE; UL/CSA (E359006) & RoHS		UL/CSA(E347392)
	MAXIMUM ACCELERATION	2.3g in all directions		
	FATIGUE VIBRATION TEST	Vibration fatigue tests, according to the IEC 61373 Class B Category 1.		

