

LVF 80

 Emergency Kit
(Standard Temperatures)

 Emergency Kit
(Low Temperatures)

	INPUT VOLTAGE	120 - 277 Vac		
	INPUT FREQUENCY (Hz)	45 - 65		
	POWER CONSUMPTION (W)	12	13	18
	LUMINOSITY (lm)	800		
	OPERATING TEMPERATURE	-30°C to +50°C	0°C to +50°C	-30°C to +50°C
	STORAGE TEMPERATURE	-40°C to +70°C	-30 °C to + 65°C	-30°C to +65°C
(* Recommended storage temperature +5°C to +25°C)				
	BATTERY LIFE	-	4 Years	4 Years
	EMERGENCY AUTONOMY & LUMINOSITY	90 min 100% flux	-	-
	BATTERY FULL CHARGE TIME (h)	-	24	24
	WEIGHT (kg)	0,75	1	1
	DIMENSIONS (mm) [LxWxH]	190 x 145 x 120		
	IP RATING	IP 65		
	IK RATING	IK 05		
	COLOR TEMPERATURE (CCT)	Cool White: 5.000 - 7.000K		
	LED WORKING LIFE	50 000 h typical		
	CERTIFICATIONS	CE; UL pending		
	MAXIMUM ACCELERATION	2.3g in all directions		

