




















	LVK 80 No Emergency Kit	 With Emergency Kit (Standard Temperatures)	 With Emergency Kit (Low Temperatures)
 INPUT VOLTAGE	120 - 277 Vac		
 INPUT FREQUENCY (Hz)	45 - 65		
 POWER CONSUMPTION (W)	12	13	Max.18
 LUMINOSITY (lm)	800		
 OPERATING TEMPERATURE	-30°C to +50°C	0°C to +50°C	-30°C to +50°C
 STORAGE TEMPERATURE	-40°C to +70°C	-30 °C to + 65°C	-30°C to +65°C
		(* Recommended storage temperature +5°C to +25°C)	
 BATTERY LIFE	-	4 Years	4 Years
 EMERGENCY AUTONOMY & LUMINOSITY	90 min 100% flux	90 min 100% flux	90 min 100% flux
 BATTERY FULL CHARGE TIME (h)	-	24	24
 WEIGHT (kg)	0,75	1	1
 DIMENSIONS (mm) [LxWxH]	190 x 145 x 120		
 IP RATING	IP 65		
 IK RATING	IK 05		
 COLOUR TEMPERATURE (CCT)	Cool White: 5.000 - 7.000K		
 LED WORKING LIFE	50 000 h typical		
 CERTIFICATIONS	CE; UL pending		
 MAXIMUM ACCELERATION	2.3g in all directions		

